Graco's new Hydra-Clean™

Powerful Cleaning for the Toughest Environment

WWW.GRACO-MEDIA.CZ

The cleaning experience by Graco®

- Fits most pressure, flow and material requirements
- Includes everything needed to use with open-head universal drums
- Designed to be used with cold or hot water up to 95°C (200°F)
- Available with an accumulator and chemical injector
- Efficient cleaning with water, detergent or chemical solutions
- Supports multiple guns

For more information, visit our website at www.graco.be

PROVEN QUALITY. LEADING TECHNOLOGY.

Process cleaning pumps

Ordering Information Accessories

GUNS AND WANDS

247879	Replacement gun/wand
15T283	Brass/stainless spray gun
15T282	Stainless steel spray gun
15T279	813mm (32 inch) stainless steel wand
15T280	254mm (10 inch) stainless steel wand
247622	Gun and suction tube holder
247880	Gun stainless steel connection

HOSES

214959	25,4mm x 1,82 M (1 inch x 6 ft) inlet hose
247878	9,52mm x 15,24 M (3/8 inch x 50 ft) outlet hose: 310 bar (4500 psi)

OTHER

15T284	60 mesh inlet strainer with 1 inch npt (f) connection
191635	10 mesh inlet strainer with 1 inch npt (f) connection

INSTRUCTION MANUAL

312585	Hydra-Clean™ Packages

Ordering Information

HIGH SANITATION CLEANING PACKAGES

PACKAGE ORDER N°	247549 OR 247550	247551 OR 247552	247553 OR 247554
Pump Assembly Part No.	N34DN0	N65DN0	N65DN0
Pump Lower Part No	247599	241648	687055
Construction	SST	SST	SST
Standard Seal Repair Kit	247881	222880	See manual 311825
Construction	UHMWPE/CF-PTFE	UHMWPE/CF-PTFE	UHMWPE/CF-PTFE
Optional Seal Repair Kits	207581	222875	222845
Construction	PTFE	UHMWPE/PTFE	UHMWPE/PTFE
Motor Repair Kit	See manual 311238	See manual 311238	See manual 311238

STAINLESS STEEL TIPS

PART N°	TIP N°	ORIFICE SIZE MM (IN.)	FAN WIDTH ANGLE AT 3 BAR (40 PSI, 0.03MPA)	CAPACITY AT 69 BAR (1000 PSI , 6,89 MPA) L / MIN (GPM)
805418	40020	0.51 (0.020)	40°	3.78 (1.00)
805422*	40030	0.76 (0.030)	40°	5.68 (1.50)
805426	40035	0.89 (0.035)	40°	6.62 (1.75)
805433*	25045	1.14 (0.045)	25°	8.52 (2.25)
805445	25060	1,52 (0.060)	25°	11.36 (3.00)
805446*	40060	1.52 (0.060)	40°	11.36 (3.00)
805450*	40065	1.65 (0.065)	40°	12.30 (3.25)
805453	25070	1.78 (0.070)	25°	13.25 (3.50)
805458	40075	1.91 (0.075)	40°	14.20 (3.75)
805459*	00080	2.03 (0.080)	0°	15.14 (4.00)
805471	00100	2.54 (0.100)	0°	18.93 (5.00)

** Tip included with pump packages*

Other orifice sizes and fan widths available from Graco, contact a sales representative for more information.

Technical Data

PUMP PACKAGE PART N°	PACKAGE TYPE	RATIO	MAX. WORKING PRESSURE BAR (MPA, PSI)	MAX. AIR INPUT PRESSURE BAR (MPA, PSI)	FLUID FLOW AT 60 CPM L / MIN (GPM)	PUMP VOLUME PER CYCLE (CC PER CYCLE)	AIR INLET SIZE	FLUID INLET SIZE	FLUID OUTLET SIZE (*)
247549	Cart Mount	12:1	86 (8.6,1250)	7.0 (0.7,100)	33 (8.7)	580 cc	3/4" npt(f)	1"	3/8"
247550	Wall Mount	12:2	86 (8.6,1250)	7.0 (0.7,100)	33 (8.7)	580 cc	3/4" npt(f)	1"	3/8"
247551	Cart Mount	23:1	157 (15.7,2275)	7.0 (0.7,100)	34,7 (9.2)	580 cc	3/4" npt(f)	1"	3/8"
247552	Wall Mount	23:1	157 (15.7,2275)	7.0 (0.7,100)	34,7 (9.2)	580 cc	3/4" npt(f)	1"	3/8"
247553	Cart Mount	30:1	211 (21.1,3065)	7.0 (0.7,100)	25,9 (6.8)	430 cc	3/4" npt(f)	1"	3/8"
247554	Wall Mount	30:1	211 (21.1,3065)	7.0 (0.7,100)	25,9 (6.8)	430 cc	3/4" npt(f)	1"	3/8"

** Includes two outlet ports per unit*

GRACO N.V. Industrieterrein Oude Bunders
Slakweidestraat 31 • B-3630 Maasmechelen
Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777
E-mail: info@graco.be • http://www.graco.be

©2008 Graco Inc. Form No. 300689E Rev. A 09/08 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

WWW.GRACO-MEDIA.CZ