

MD2 Dispense Valve

For Accurate Two-Component Dispensing



Designed to accurately dispense and mix plural-component sealants and adhesives

- Minimizes maintenance time and costs while maximizing dispense time
- Designed with fewer parts and is easy to clean
- Streamlines maintenance and service
- Complete modular design adapts to different installation needs
- No unique tools required
- Handles a wide range of materials



Ordering Information

Graco MD2 Dispense Valve

Valve Options

255179 1:1 soft seat, adjustable snuff-back
255180 1:1 hard seat, non-adjustable snuff-back
255181 Wide ratio, soft seat, adjustable snuff-back
255182 Wide ratio, hard seat,

non-adjustable snuff-back

Manual Gun Options

255442 1:1 hard seat, air-actuated gun, trigger
255445 Wide ratio, hard seat, air-actuated gun, trigger
255443 1:1 hard seat, electrically-actuated

counter-balanced valve, trigger

255446 Wide ratio, hard seat, electrically-actuated gun, trigger

255444 1:1 hard seat, electrically-actuated counter-balanced valve, lever

255447 Wide ratio, hard seat,

electrically-actuated gun, lever

LC0004 1:1 soft seat, electrically-actuated counter-balanced valve, trigger

LC0006 Wide ratio, soft seat, electrically-actuated gun, trigger

LC0005 1:1 soft seat, electrically-actuated

counter-balanced valve, lever

LC0007 Wide ratio, soft seat,

electrically-actuated gun, lever

Manual Gun Options

255220 MD2 hard seat rebuild kit, needle and nose

255219 MD2 soft seat rebuild kit,

needle and nose

255218 MD2 rebuild kit, back-end of wet section

255217 MD2 rebuild kit, air cylinder255208 Electric switch handle255206 Pneumatic switch handle

255249 Actuated lever

255273 Hanger adapter

GRACO N.V. Industrieterrein Oude Bunders
Slakweidestraat 31

B-3630 Maasmechelen
Tel: +32 (89) 770 700

Fax: +32 (89) 770 777

E-mail: info@graco.be


http://www.graco.be

©2007 Graco Inc. Form No. 339117E Rev. A 10/07 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Ideal for Most Two-Component Dispensing Applications

Technical Specifications

	MD2 VALVE
Maximum fluid pressure	207 bar (20.7 MPa, 3000 psi)
Maximum cylinder air pressure	8.4 bar (0.84 MPa, 120 psi)
Minimum air cylinder actuating pressure	2.8 bar (0.3 MPa, 40 psi)
Maximum working fluid temperature	60°C (140°F)
Wetted parts	stainless steel, carbide, UHMWPE, acetal,
	PEEK, PTFE
Gun weight	255179 0.66 kg (1.45 lbs) 255180 0.66 kg (1.45 lbs) 255181 0.68 kg (150 lbs) 255182 0.68 kg (150 lbs)
Dimensions	168.7 mm L x 59 mm W x 57 mm D (6.64 in L x 2.32 in W x 2.25 in D)
Fluid inlets	9/16-18 UNF (f) (06 SAE)
Air inlets	1/8 in npt (f)
Instruction manual	312185



Lever-Actuated

Dispense Valve